

W20-1
48" x 48"

ROAD
WORK
FT

W20-4
48" x 48"

ONE LANE
ROAD
FT

W20-7a(1)
48" x 48"



BUFFER

NOTE: ACCESS POINTS WITHIN LANE CLOSURE
SHALL BE CONTROLLED BY FLAGGER(S)

REFER TO TCP 100.01 FOR SIGN
SPACING, TAPER LENGTHS AND
BUFFER LENGTHS

50' TO 100'

WORK AREA

BUFFER

50' TO 100'

W20-7a(1)
48" x 48"

W20-4
48" x 48"

W20-1
48" x 48"

ONE LANE
ROAD
FT

ROAD
WORK
FT

DY CL

B

A

BUFFER

DY CL

← DIRECTION OF TRAFFIC

.. SIGN

▨ WORK SITE

● FLAGGER

○ TRAFFIC DRUMS
OR CONES

S¹=30 FT.

S²=10 FT.

DATE

07-01-04

DES. BY

MCDPWT

DRAWN BY

TCLE

SCALE

NTS

TRAFFIC OPERATIONS SECTION
MONTGOMERY COUNTY, MARYLAND

FLAGGING CONTROL AT
3 - LEG INTERSECTION
FAR - SIDE CLOSURE

APPROVED

CHIEF, TRAFFIC OPERATIONS SECTION

STANDARD TCP-105.07 ____ OF ____ SHEETS

REVISION BY	DATE	APPROVED